

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 1 083 129 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
14.03.2001 Bulletin 2001/11

(51) Int Cl.7: **B65D 23/08**

(21) Application number: **99870181.7**

(22) Date of filing: **10.09.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

- **Etesse, Patrick Jean-Francois**  
1040 Brussel (BE)
- **Johnson, Karen Amanda**  
1060 Brussel (BE)
- **Moss, Gates Markham**  
Cincinnati, Ohio 45242 (US)

(71) Applicant: **THE PROCTER & GAMBLE COMPANY**  
Cincinnati, Ohio 45202 (US)

(74) Representative: **Engisch, Gautier et al**  
**BVBA Procter & Gamble Europe SPRL,**  
Temseleaan 100  
1853 Strombeek-Bever (BE)

(72) Inventors:  
• **Blake, Alan David**  
3090 Overijse (BE)

(54) **Shrink sleeved bottle**

(57) The invention relates to a bottle (1) having a base, a top part and sides, the bottle comprising a handle (2) located on a side of the bottle, the bottle being shrink-sleeved (3), whereby the sleeve does not cover the handle.




Figure 2

**EP 1 083 129 A1**

## Description

### Technical Field

**[0001]** The invention relates to packages such as bottles used for containing fluids.

### Background of the Invention

**[0002]** Bottles are widely used in consumer goods industry for packaging various type of fluid products. Such bottles are normally decorated, often using labels which are stuck onto the bottle. Such labels are typically used not only for decoration but also to display usage instructions or information on the composition of the content for example. However, conventional labelling technology such as wet glue labels, self-adhesive labels, or in mold labels do not allow to decorate the full bottle surface area. The accumulation of such visual signals led the industry to develop new approaches allowing higher decoration coverage of the container's surface, one of them being the shrink-sleeving of packages.

**[0003]** Shrink-sleeving is mostly used in the drinking industry, whereby a sleeve of thermo-plastic material may be shrunk all around a beverage bottle, thus offering an extended area which may be used for any type of graphics. Typical thermoplastic materials used for shrink sleeving include polyvinylchloride (PVC), polyesterteraphtalate (PET), oriented polypropylene (OPP) and oriented polystyrene (OPS).

**[0004]** However, use of shrink-sleeving did not extend to relatively larger containers, particularly because of the need of a side handle when such containers are used. Indeed, the sleeving of a bottle consists in inserting the bottle into a straight sleeve of thermo-plastic material, the thermo-plastic being then heated up to shrink and fit tightly around the container. Clearly, in case of a container or bottle having a side handle, such a process would lead to preventing access to the handle as the sleeve would cover the recess produced by the handle, so that the handle cannot be gripped.

**[0005]** The invention seeks to provide a bottle with a side handle, whereby the surface available for displaying graphics onto the bottle is maximised.

### Summary of the Invention

**[0006]** In accordance with the invention, this object is accomplished in a bottle having a base, a top part and sides, the bottle comprising a handle located on a side of the bottle, the bottle being shrink-sleeved, whereby the sleeve does not cover the handle.

### Detailed Description of the Invention

**[0007]** The invention relates to a decorated bottle where the means of decoration is a shrink sleeve. The term bottle hereby should be understood generally as a

container for fluid products, fluid products including liquids as well as flowing materials such as powders or granule.

The bottle has a base. By a base it should be understood a part of the bottle on which the bottle is left to stand upright. This part may be flat, or may for example be formed from a moulded tripod, or from a flat ring. Many types of "base" are known in the art, the main feature of such a base being to hold the bottle in a stable position on a flat supporting surface.

The bottle further comprises a top part. The top part is typically the part of the bottle opposed to the base. The top is commonly the part of the bottle which provides an exit for the content of the bottle.

The bottle also comprises sides. The sides are the surfaces which generally speaking are joining the top and the base of the bottle. Typically, when the bottle is upright, the sides are substantially vertical and perpendicular to the base. The sides may also have a curved or relatively complex shape depending on the bottle considered.

The bottle comprises a handle located on a side of the bottle. This makes the bottle different from bottles without handles (such as for example bottles for soda or beer portions), and also from bottle with a handle on the top part (such as "heavy" bottles of the type used for containing more than 5 liters of petrol for example). The handle according to the invention is normally forming a recess in the vertical direction when the bottle is upright, the recess being such that a user may slide the hand in the recess to hold the bottle by the handle.

Further, the bottle is shrink-sleeved. Shrink sleeving consists in enveloping a part of the bottle in a thermo-plastic tube like sleeve, the sleeve being heated to shrink and fit onto the bottle.

**[0008]** According to the invention, the sleeve does not cover the handle. This conveniently reduces the likelihood of contact between a consumer hand and the sleeve cut-out fringe when gripping the handle. As a matter of fact, the sleeve fringe can exhibit sharp edges which can result in paper cut to consumer hands or simply unpleasant contact. In this manner, access to the handle is easy and direct, the user gripping directly the handle itself, without being in contact with the sleeve.

**[0009]** Such a result may be obtained in various ways.

**[0010]** In a first embodiment, the handle may simply be assembled to the bottle. This may be obtained for example with a clip on handle, or with a handle integrated to a transition piece such as a non-dripping neck for example. Indeed, if this is achieved, the bottle may be sleeved prior to assembling or placing the handle onto the bottle.

**[0011]** In another embodiment, the handle is an integral part of the bottle, the handle merging with the side of the bottle in two regions, whereby the sleeve is cut out between the two merging regions. In this manner, the sleeve does not cover the handle. In this particular

case, the recess formed by the handle has a closed perimeter. In such an embodiment, it might be preferable to cut out the sleeve onto the bottle after the heat shrink operation has been performed. The cutting of the sleeve can be achieved by various means such as mechanical die cutting, laser cutting or water jet cutting. This allows to remove that portion of the sleeve which covers the handle hence exposing the handle area for convenient gripping by sliding the hand through the handle.

[0012] In another embodiment, the handle is an integral part of the bottle, the handle merging with the side of the bottle in one region only, the sleeve being cut out in the merging region. In such an embodiment, the cut out in the sleeve should preferably have a surface at least equal or larger than the largest cross section of the handle, so that the sleeve may be placed onto the bottle prior to shrinking, the cut out being slipped onto the handle, the sleeve being shrunk thereafter. In such an embodiment, the cut-out has a closed perimeter. It should be noted that the cut out may have a surface slightly smaller than the cross section of the handle where the handle merges with the side of the bottle.

[0013] In another embodiment, the handle is an integral part of the bottle, the handle merging with the side of the bottle in one region only, the sleeve covering the sides of the bottle from the base up to the merging region, or whereby the sleeve covers the sides of the bottle from the top down to the merging region. In such a case, there is not a particular need for a cut out for example as the sleeve is simply positioned from the top or from the base up to the region where the handle merges with the side of the bottle. However, a cut out may be provided, the cut out having in this case a non-closed perimeter, whereby the sleeve may be slipped on the bottle beyond the region where the handle merges with the side. The cut out in this case is an indent in the sleeve allowing the sleeve to reach beyond the merging region mentioned above.

[0014] In another embodiment, the handle is an integral part of the bottle, the handle merging with the side of the bottle in one region only, a first sleeve covering the sides of the bottle from the base up to the merging region, and whereby a second sleeve covers the sides of the bottle from the top down to the merging region. This embodiment corresponds to a combination of the two previous embodiments, and has the advantage to allow coverage by the sleeve of a larger part of the bottle.

[0015] In the preferred embodiments, the sleeve covers at least 30% of the outer surface of the bottle, in order to provide for a sufficient surface to application of graphics. More preferably, the sleeve covers at least 50% of the outer surface of the bottle, even more preferably 65%, and most preferably at least 80% of the outer surface of the bottle. It should be understood the "outer surface of the bottle" hereby comprises the whole outer surface, including the outer surface of the base, or of the handle for example.

[0016] In the preferred embodiments, the bottle has an internal volume of at least 1 litre and of less than 5 litres. Even more preferred is a bottle with an internal volume of less than 3 litres. Indeed, a handle would not be particularly needed for smaller bottles, and a side handle would be preferably replaced by a top handle for larger bottles.

[0017] The invention will now be described by way of example and with reference to the accompanying drawing in which:

[0018] Figure 1 is a side view illustrating a sleeved bottle (1) according to the invention, the handle (2) merging with the side of the bottle in two regions, whereby the sleeve (3) (which is hatched on the Figures) is cut-out between the two merging regions.

[0019] Figure 2 is a front view of the bottle of Figure 1.

[0020] Figure 3 is a side view illustrating a sleeved bottle (1) according to the invention, the handle (2) merging with the side of the bottle in the top region only, the sleeve (3) being cut out (4) in the merging region.

[0021] Figure 4 is a front view of the bottle of Figure 3.

[0022] Figure 5 is a side view illustrating a sleeved bottle (1) according to the invention, the handle (2) merging with the side of the bottle (1) in top region only and the sleeve (3) covering the sides of the bottle from the base up to the merging region.

[0023] Figure 6 is a front view of the bottle of Figure 5.

### Claims

1. A bottle having a base, a top part and sides, the bottle comprising a handle located on a side of the bottle, the bottle being shrink-sleeved, whereby the sleeve does not cover the handle.
2. The bottle according to claim 1, whereby the handle is assembled to the bottle.
3. The bottle according to claim 1, whereby the handle is an integral part of the bottle.
4. The bottle according to claim 3, whereby the handle merges with the side of the bottle in two regions, and whereby the sleeve is cut out between the two merging regions.
5. The bottle according to claim 3, whereby the handle merges with the side of the bottle in one region only.
6. The bottle according to claim 5, whereby the sleeve is cut out in the merging region.
7. The bottle according to claim 5, whereby the sleeve covers the sides of the bottle from the base up to the merging region, or whereby the sleeve covers the sides of the bottle from the top down to the merging region.

8. The bottle according to claim 5, whereby a first sleeve covers the sides of the bottle from the base up to the merging region, and whereby a second sleeve covers the sides of the bottle from the top down to the merging region.

5

9. The bottle according to any of the above claims, whereby the sleeve covers at least 30% of the outer surface of the bottle.

10

10. The bottle according to any of the above claims, whereby the bottle has an internal volume of at least 1 litre and of less than 5 litres.

15

20

25

30

35

40

45

50

55




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 99 87 0181

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 609 644 A (PROCTER & GAMBLE) 10 August 1994 (1994-08-10) * column 5, line 34 - line 38; claim 1 * * column 5, line 56 - column 6, line 3; figure 2 *	1,3,4,9, 10	B65D23/08
X	EP 0 785 146 A (A K TECH LAB INC) 23 July 1997 (1997-07-23) * column 2, line 25 - line 33; figures 1,3,4 * * column 3, line 15 - line 18 *	1,2	
X	EP 0 609 575 A (PROCTER & GAMBLE) 10 August 1994 (1994-08-10) * column 5, line 45 - line 52 * * column 6, line 29 - line 30; figure 3 *	1,3,4,9, 10	
A	US 4 629 598 A (THOMPSON MORTIMER S) 16 December 1986 (1986-12-16) * figures 4,5 *	1,3,5	
A	EP 0 483 976 A (OWENS ILLINOIS PLASTIC PROD) 6 May 1992 (1992-05-06) * figure 5 *	1,3,5	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7) B65D
Place of search THE HAGUE		Date of completion of the search 25 January 2000	Examiner Mr Luca del Monte
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1500 03 82 (P/C01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 87 0181

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-01-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0609644 A	10-08-1994	AU 6130294 A	29-08-1994
		AU 6297094 A	29-08-1994
		CA 2155113 A	18-08-1994
		CA 2155114 A,C	18-08-1994
		DE 69304040 D	19-09-1996
		DE 69304040 T	20-03-1997
		EP 0609575 A	10-08-1994
		ES 2091587 T	01-11-1996
		JP 8509190 T	01-10-1996
		JP 8509447 T	08-10-1996
		TR 27494 A	07-06-1995
		WO 9417982 A	18-08-1994
		WO 9418076 A	18-08-1994
		US 5524787 A	11-06-1996
		US 5711061 A	27-01-1998
EP 0785146 A	23-07-1997	JP 2617815 B	04-06-1997
		JP 4270628 A	28-09-1992
		AT 158774 T	15-10-1997
		DE 69127804 D	06-11-1997
		DE 69127804 T	29-01-1998
		DK 498123 T	27-10-1997
		EP 0498123 A	12-08-1992
		ES 2108037 T	16-12-1997
		GB 2278802 A,B	14-12-1994
		GR 3025567 T	31-03-1998
		CN 1062878 A,B	22-07-1992
		GB 2251844 A,B	22-07-1992
		HK 114696 A	12-07-1996
		HK 114796 A	12-07-1996
		KR 9610303 B	30-07-1996
		MX 9102692 A	01-06-1992
		US 5297686 A	29-03-1994
		US 5783138 A	21-07-1998
		CA 2073083 A,C	01-03-1993
EP 0609575 A	10-08-1994	EP 0609644 A	10-08-1994
		AU 6130294 A	29-08-1994
		CA 2155113 A	18-08-1994
		JP 8509190 T	01-10-1996
		TR 27494 A	07-06-1995
		WO 9417982 A	18-08-1994
		AU 6297094 A	29-08-1994
		CA 2155114 A,C	18-08-1994
		DE 69304040 D	19-09-1996
		DE 69304040 T	20-03-1997

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 87 0181

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-01-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0609575 A		ES 2091587 T	01-11-1996
		JP 8509447 T	08-10-1996
		WO 9418076 A	18-08-1994
		US 5524787 A	11-06-1996
		US 5711061 A	27-01-1998
US 4629598 A	16-12-1986	US 4280859 A	28-07-1981
		US 4257525 A	24-03-1981
		US 4273246 A	16-06-1981
		US 4372454 A	08-02-1983
EP 0483976 A	06-05-1992	AU 647224 B	17-03-1994
		US 5086937 A	11-02-1992
		AT 150720 T	15-04-1997
		AU 9006391 A	08-07-1993
		CA 2052963 A	10-04-1992
		DE 69125337 D	30-04-1997
		ES 2098329 T	01-05-1997
		US 5383779 A	24-01-1992
		US 5275780 A	04-01-1994

EPO FORM P0456

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82